

Battery Specifications - V-Twin Line - Factory Activated Maintenance Free (AGM)

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	CA†	Apprx. Weight w/ Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
									Length	Width	Height	Length	Width	Height	
VT14L-BS-FS	12	12	150	275	10.6	—	1.4	16	6	3 7/16	5 3/4	150	87	145	[Diagram]
VT19-BS-FS	12	19	190	400	14.7	—	1.9	15	6 7/8	4	6 1/8	175	101	157	[Diagram]
VT19L-BS-FS	12	19	190	400	14.7	—	1.9	15	6 7/8	4	6 1/8	175	101	157	[Diagram]
VT20H-BS-FS	12	20	290	460	14.6	—	2.0	15	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VT20HL-BS-FS	12	20	290	460	14.6	—	2.0	15	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VT30HL-BS-FS	12	30	400	530	21.6	—	3.0	15	6 9/16	5	6 7/8	166	126	175	[Diagram]
VT32HL-BS-FS	12	32	420	560	22.9	—	3.2	15	6 9/16	5	6 7/8	166	126	175	[Diagram]

Battery Specifications - Factory Activated Maintenance Free (AGM)

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	CA†	Apprx. Weight w/ Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
									Length	Width	Height	Length	Width	Height	
VTX4B-BS-FS	12	2.3	30	80	2.1	—	0.3	13	4 1/2	1 9/16	3 7/16	114	39	86	[Diagram]
VTX4L-BS-FS	12	3	40	130	3.3	—	0.4	5	4 1/2	2 13/16	3 3/8	114	71	86	[Diagram]
VTX5S	12	4	50	150	4.2	—	0.3	5	4 7/16	2 3/4	3 1/3	113	70	85	[Diagram]
VTX5L-BS-FS	12	4	65	150	4.4	—	0.5	5	4 1/2	2 13/16	4 3/16	114	71	106	[Diagram]
VTX6.5L-BS-FS	12	6.5	60	145	5.2	—	0.65	5	5 1/2	2 5/8	4	139	66	102	[Diagram]
VTX7S	12	6	75	210	5.2	—	0.6	5	4 7/16	2 3/4	4 1/8	113	70	105	[Diagram]
VTX7A-BS-FS	12	6	85	175	5.9	—	0.7	5	6	3 7/16	3 3/4	150	87	94	[Diagram]
VTX7B-4	12	6	85	230	5.6	—	0.6	11	6	2 9/16	3 11/16	150	65	93	[Diagram]
VTX7L-BS-FS	12	6	80	130	5.5	—	0.6	5	4 1/2	2 13/16	5 3/16	114	71	131	[Diagram]
VTX8V	12	7	80	215	6.0	—	0.7	5	4 1/2	2 13/16	5 3/16	114	71	131	[Diagram]
VTX9B-4	12	8	100	280	6.7	—	0.8	11	6	2 3/4	4 1/8	150	70	105	[Diagram]
VTX9-BS-FS	12	8	90	215	7.2	—	0.9	5	6	3 7/16	4 3/16	150	87	105	[Diagram]
VTX9-B-FS	12	9	95	160	6.5	—	0.9	6	5 5/16	3	5 1/2	135	75	139	[Diagram]
VTX10S	12	8.5	130	285	7.4	—	0.9	11	6	3 7/16	3 11/16	150	87	93	[Diagram]
VTX12A-BS-FS	12	10	120	225	7.5	—	1.0	11	6	3 7/16	4 3/16	150	87	105	[Diagram]
VT12B-4	12	10.5	115	280	8.4	—	1.0	11	6	2 3/4	5 1/8	150	69	130	[Diagram]
VTX12-BS-FS	12	10	120	260	9.1	—	1.2	5	6	3 7/16	5 1/8	150	87	130	[Diagram]
VTX12S	12	11	140	340	9.2	—	1.1	11	6	3 7/16	4 3/8	150	87	110	[Diagram]
VTX12A-A-FS	12	12	120	230	10.0	—	1.2	6	5 5/16	3 3/16	6 5/16	134	80	160	[Diagram]
VTX14S	12	12	140	340	9.2	—	1.2	11	6	3 7/16	4 3/8	150	87	110	[Diagram]
VT14B-4	12	12	135	270	9.7	—	1.2	11	6	2 3/4	5 3/4	150	70	145	[Diagram]
VTX14-BS-FS	12	12	150	275	10.6	—	1.4	4	6	3 7/16	5 3/4	150	87	145	[Diagram]
VTX14AH-BS-FS	12	12	160	340	11.4	—	1.4	4	5 5/16	3 9/16	6 3/8	135	90	161	[Diagram]
VTX14AHL-BS-FS	12	12	160	340	11.4	—	1.4	4	5 5/16	3 9/16	6 3/8	135	90	161	[Diagram]
VTX15L-BS-FS	12	13	180	320	11.1	—	1.3	4	6 7/8	3 7/16	5 1/8	175	87	130	[Diagram]
VTX16H	12	16	240	320	10.7	—	1.6	4	6	3 7/16	5 3/4	150	87	145	[Diagram]
VTX19CL-BS-FS	12	21	210	415	17.1	—	2.1	5	6 7/8	4	6 7/8	175	101	175	[Diagram]
VTX20-BS-FS	12	18	200	405	14.1	—	1.8	4	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VTX20L-BS-FS	12	18	200	405	14.1	—	1.8	4	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VTX20CH-BS-FS	12	18	180	295	12.6	—	1.8	4	6	3 7/16	6 3/8	150	87	161	[Diagram]
VTX24HL-BS-FS	12	21	230	400	17.4	—	2.1	4	8 1/8	3 7/16	6 7/8	205	86	161	[Diagram]
VTX30CL-BS-FS	12	30	280	505	23.9	—	3.0	5	6 9/16	5	7 5/8	166	126	194	[Diagram]
VTX30L-BS-FS	12	28	280	505	20.3	—	2.8	5	6 9/16	5	6 7/8	166	126	175	[Diagram]
VTX11U1-LD-FS	12	32	300	495	22.7	—	3.2	14	7 3/4	5 1/4	7 7/16	196	131	186	[Diagram]
VTX51913-FS*	12	19	170	325	13.9	—	1.9	10	7 7/16	3 1/4	6 7/8	186	82	171	[Diagram]
VTX26RH-FS	12	40	540	595	32.8	—	4.0	17	7 3/4	6 1/2	7 3/4	196	165	197	[Diagram]

† Cranking value determined by the use of a hand held tester. Individual test results may vary.
 * Maintenance Free Gel Technology

Due to the self-discharge characteristics of factory activated lead acid batteries, it is imperative that they be charged every 4-6 months during storage, otherwise permanent loss of capacity might occur as a result of sulfation. To prolong shelf life without charging, store batteries at 50°F (10°C) or less.

Battery Specifications - Sealed Maintenance Free (AGM)

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	CA†	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
									Length	Width	Height	Length	Width	Height	
VTX4B-BS	12	2.3	30	2.0	4.1	0.3	0.3	13	4 1/2	1 9/16	3 7/16	114	39	86	[Diagram]
VTR4A-BS	12	2.3	30	2.2	4.7	0.3	0.3	12	4 1/2	1 15/16	3 3/8	114	49	86	[Diagram]
VTX4L-BS	12	3	40	3.1	6.1	0.4	0.4	5	4 1/2	2 13/16	3 3/8	114	71	86	[Diagram]
VTX5L-BS	12	4	55	3.8	8.1	0.5	0.5	5	4 1/2	2 13/16	4 3/16	114	71	106	[Diagram]
VTX6.5L-BS	12	6.5	60	4.3	12.8	0.65	0.65	5	5 1/2	2 5/8	4	139	66	102	[Diagram]
VTX7A-BS	12	6	85	4.9	11.2	0.7	0.7	5	6	3 7/16	3 3/4	150	87	94	[Diagram]
VTX7L-BS	12	6	75	4.5	11.2	0.6	0.6	5	4 1/2	2 13/16	5 3/16	114	71	131	[Diagram]
VTX9-BS	12	8	90	5.9	13.5	0.9	0.9	5	6	3 7/16	4 3/16	150	87	105	[Diagram]
VTX9-B-BS	12	9	90	6.0	18.9	0.9	0.9	6	5 5/16	3	5 1/2	135	75	139	[Diagram]
VTX12A-BS	12	10	120	6.7	15.9	1.0	1.0	11	6	3 7/16	4 3/16	150	87	105	[Diagram]
VTX12-BS	12	10	160	7.7	20.3	1.2	1.2	5	6	3 7/16	5 1/8	150	87	130	[Diagram]
VTX14-BS	12	12	180	9.1	23.3	1.4	1.4	4	6	3 7/16	5 3/4	150	87	145	[Diagram]
VTX14L-BS	12	12	180	9.1	23.3	1.4	1.4	4	6	3 7/16	5 3/4	150	87	145	[Diagram]
VTX14AH-BS	12	12	160	9.1	22.3	1.4	1.4	4	5 5/16	3 9/16	6 3/8	135	90	161	[Diagram]
VTX14AHL-BS	12	12	160	9.1	22.3	1.4	1.4	4	5 5/16	3 9/16	6 3/8	135	90	161	[Diagram]
VTX15L-BS	12	13	180	10.5	23.3	1.3	1.3	4	6 7/8	3 7/16	5 1/8	175	87	130	[Diagram]
VTX16-BS	12	14	200	10.8	26.4	1.4	1.4	4	6	3 7/16	6 3/8	150	87	161	[Diagram]
VTX16-BS-1	12	14	200	10.8	26.4	1.4	1.4	1	6	3 7/16	6 3/8	150	87	161	[Diagram]
VTX19-BS	12	19	190	14.3	32.5	1.2	1.2	6	6 7/8	4	6 1/8	175	101	157	[Diagram]
VTX19L-BS	12	19	190	14.3	32.5	1.2	1.2	6	6 7/8	4	6 1/8	175	101	157	[Diagram]
VTX19CL-BS	12	21	210	16.5	32.5	1.2	1.2	5	6 7/8	4	6 7/8	175	101	175	[Diagram]
VTX20-BS	12	18	210	12.7	31.4	1.8	1.8	4	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VTX20L-BS	12	18	210	12.7	31.4	1.8	1.8	4	6 7/8	3 7/16	6 1/8	175	87	155	[Diagram]
VTX20CH-BS	12	18	220	11.6	27.7	1.8	1.8	4	6	3 7/16	6 3/8	150	87	161	[Diagram]
VTX24H-BS	12	21	240	15.6	33.5	2.1	2.1	4	8 1/8	3 7/16	6 7/8	205	86	161	[Diagram]
VTX24HL-BS	12	21	240	15.6	33.5	2.1	2.1	4	8 1/8	3 7/16	6 7/8	205	86	161	[Diagram]
VTX30CL-BS	12	30	280	18.9	55.5	2.8	2.8	5	6 9/16	5	7 5/8	166	126	194	[Diagram]
VTX30L-BS	12	28	280	18.9	55.5	2.8	2.8	5	6 9/16	5	6 7/8	166	126	175	[Diagram]

Battery Specifications - Low Maintenance

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
								Length	Width	Height	Length	Width	Height	
CB16-B-LM	12	19	230	10.6	40.6	1.9	6	6 7/8	4	6 1/8	175	100	155	
C50-N18L-A-LM	12	20	220	10.3	47.3	2.0	7	8 1/8	3 9/16	6 7/8	205	90	162	

Battery Specifications - High Performance

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
								Length	Width	Height	Length	Width	Height	
CB2.5L-C	12	2.5	20	1.9	8.1	0.3	—	3 3/16	2 3/4	4 1/8	80	70	105	
CB3L-A	12	3	32	2.3	8.1	0.3	6	3 7/8	2 1/4	4 3/8	98	56	110	
CB3L-B	12	3	32	2.3	8.1	0.3	6	3 7/8	2 1/4	4 3/8	98	56	110	
CB4L-A	12	4	40	2.6	10.1	0.4	5	4 3/4	2 3/4	3 5/8	120	70	92	
CB4L-B	12	4	40	2.6	10.1	0.4	5	4 3/4	2 3/4	3 5/8	120	70	92	
CB5L-B	12	5	50	3.2	12.2	0.5	6	4 3/4	2 3/8	5 1/8	120	60	130	
CB7-A	12	8	90	4.7	20.3	0.8	6	5 5/16	3	5 1/4	135	75	133	
CB7B-B	12	7	70	4.0	15.9	0.7	6	6	2 3/8	5 1/8	150	60	130	
CB7C-A	12	8	80	5.2	20.3	0.8	1	5 1/8	3 9/16	4 1/2	130	90	114	
CB7L-B	12	8	90	4.7	20.3	0.8	3	5 5/16	3	5 1/4	135	75	133	
CB9-B	12	9	90	4.8	20.3	0.9	6	5 5/16	3	5 1/2	135	75	139	
CB9L-B	12	9	90	4.8	20.3	0.9	6	5 5/16	3	5 1/2	135	75	139	
CB9L-A2	12	9	90	4.8	20.3	0.9	2	5 5/16	3	5 1/2	135	75	139	
CB9A-A	12	9	90	5.0	20.3	0.9	6	5 5/16	3	6 1/8	135	75	155	
CB10A-A2	12	11	140	6.2	27.0	1.1	8	5 5/16	3 9/16	6 1/8	135	90	155	
CB10L-A2	12	11	140	6.2	27.0	1.1	8	5 5/16	3 9/16	5 3/4	135	90	145	
CB10L-B	12	11	140	6.2	27.0	1.1	6	5 5/16	3 9/16	5 3/4	135	90	145	
CB10L-B2	12	11	140	6.2	27.0	1.1	8	5 5/16	3 9/16	5 3/4	135	90	145	
CB12A-A†	12	12	135	7.0	27.0	1.2	6	5 5/16	3 3/16	6 5/16	134	80	160	
CB12A-B	12	12	135	7.0	25.4	1.2	6	5 5/16	3 3/16	6 5/16	134	80	160	
CB12AL-A	12	12	135	7.0	25.4	1.2	6	5 5/16	3 3/16	5 5/16	134	80	160	
CB12AL-A2	12	12	135	7.0	25.4	1.2	8	5 5/16	3 3/16	6 5/16	134	80	160	
CB12B-B2	12	13	145	7.5	27.0	1.2	8	6 5/16	3 9/16	5 1/8	160	90	130	
CB12C-A	12	13	135	7.1	27.0	1.2	4	5 5/16	3 3/16	6 7/8	134	80	175	
CB14-A2	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
CB14-B2	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
CB14A-A1	12	14	160	7.8	30.4	1.4	6	5 5/16	3 1/2	6 15/16	134	89	176	
CB14A-A2	12	14	160	7.8	30.4	1.4	8	5 5/16	3 1/2	6 15/16	134	89	176	
CB14L-A1	12	14	160	7.7	30.4	1.4	1	5 5/16	3 1/2	6 9/16	134	89	166	
CB14L-A2	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
CB14L-B2	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
SCB14L-A2 ▲	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
SCB14L-B2 ▲	12	14	160	7.7	30.4	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
CB16AL-A2	12	16	190	8.7	37.2	1.6	2	8 1/8	2 13/16	6 7/16	207	71.5	164	
CB16B-A	12	16	180	8.2	33.8	1.6	4	6 5/16	3 9/16	6 3/8	160	90	161	
CB16B-A1	12	16	180	8.2	33.8	1.6	7	6 5/16	3 9/16	6 3/8	160	90	161	
HCB16A-AB	12	16	140	8.4	30.4	1.6	7	6	3 5/8	7 1/16	151	91	180	
CB16-B	12	19	230	10.6	40.6	1.9	6	6 7/8	4	6 1/8	175	100	155	
CB16L-B†	12	19	230	10.6	40.6	1.9	6	6 7/8	4	6 1/8	175	100	155	
CB16CL-B	12	19	230	10.8	40.6	1.9	5	6 7/8	4	6 7/8	175	100	175	
CB18-A	12	18	190	9.3	40.6	1.8	7	7 1/8	3 9/16	6 3/8	180	90	162	
CB18L-A	12	18	190	9.3	40.6	1.8	7	7 1/8	3 9/16	6 3/8	180	90	162	
C50-N18A-A	12	20	220	10.4	50.7	2.0	7	8 1/8	3 9/16	6 15/16	205	90	176	
C50-N18L-A3	12	20	220	10.4	47.3	2.0	4	8 1/8	3 9/16	6 3/8	205	90	162	
SC50-N18L-AT▲	12	20	220	10.4	47.3	2.0	7	8 1/8	3 9/16	6 3/8	205	90	162	
C60-N24L-A	12	28	280	13.1	57.5	2.8	3	7 1/4	4 7/8	6 7/8	184	124	175	
C60-N24AL-B	12	28	280	13.1	57.5	2.8	3	7 1/4	4 7/8	6 7/8	184	124	175	
51814	12	19*	150	11.0	33.8	1.3	10	7 7/16	3 1/4	6 7/8	186	82	171	
51913	12	19*	150	11.0	33.8	1.9	10	7 7/16	3 1/4	6 7/8	186	82	171	
53030	12	30*	280	13.2	54.1	3.0	10	7 7/16	5 1/8	6 7/8	186	130	171	
CB30CL-B	12	30	300	15.9	57.5	3.0	4	6 5/8	5 3/16	7 9/16	168	132	192	
CB30L-B	12	30	300	15.8	57.5	3.0	4	6 5/8	5 3/16	6 15/16	168	132	176	

▲ This battery includes a sensor
† Sensor available for this battery

* @ 20 hr. rate



Battery Specifications - Conventional 6 Volt

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
								Length	Width	Height	Length	Width	Height	
6N2-2A	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	3 3/4	70	47	96	
6N2-2A-1	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	3 3/4	70	47	96	
6N2-2A-3	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	3 3/4	70	47	96	
6N2-2A-4	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	3 3/4	70	47	96	
6N2-2A-8	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	3 3/4	70	47	96	
6N2A-2C	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	4 3/16	70	47	106	
6N2A-2C-3	6	2	20	1.0	3.4	0.2	—	2 3/4	1 7/8	4 3/16	70	47	106	
6N4-2A	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4-2A-2	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4-2A-3	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4-2A-4	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4-2A-5	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4-2A-8 (6)	6	4	25	1.4	6.8	0.4	—	2 13/16	2 13/16	3 3/4	71	71	96	
6N4A-4D	6	4	35	1.5	6.8	0.4	—	2 3/8	2 1/4	5 1/8	61	57	131	
6N4B-2A	6	4	24	1.3	6.8	0.4	—	4	1 7/8	3 3/4	102	48	96	
6N4B-2A-3	6	4	24	1.3	6.8	0.4	—	4	1 7/8	3 3/4	102	48	96	
6N5.5-1D	6	5.5	40	1.9	10.1	0.6	—	3 9/16	2 3/4	3 15/16	90	70	100	
6N6-1B	6	6	48	1.9	10.1	0.6	—	3 7/8	2 1/4	4 3/8	99	57	111	
6N6-3B	6	6	48	1.8	10.1	0.6	6	3 7/8	2 1/4	4 3/8	99	57	111	
6N6-3B-1	6	6	48	1.8	10.1	0.6	6	3 7/8	2 1/4	4 3/8	99	57	111	
6N6-1D-2	6	6	48	1.9	10.1	0.6	—	3 7/8	2 1/4	4 3/8	99	57	111	
B38-6A	6	13	104	3.5	21.0	1.3	6	4 11/16	3 1/4	6 15/16	119	83	161	
B39-6	6	7	60	2.2	10.1	0.7	6	4 15/16	1 7/8	4 15/16	126	48	126	
B49-6	6	10	80	3.1	18.3	1.0	6	3 3/5	3 1/4	6 1/4	91	83	160	
B54-6	6	12	96	3.8	16.9	1.2	6	6 1/8	2 1/4	4 9/16	156	57	116	
6CB8L-B	6	8	64	2.8	10.5	0.8	6	4 3/4	2 3/4	3 3/4	120	70	95	
6N11-2D	6	11	88	3.4	13.5	1.1	6	5 7/8	2 3/4	3 15/16	150	70	100	
6N11A-1B	6	11	88	2.8	13.5	1.1	6	4 13/16	2 7/16	5 1/8	122	62	131	
6N12A-2D	6	12	96	3.2	15.2	1.2	6	6 1/8	2 1/4	4 9/16	156	57	116	

Battery Specifications - Conventional 12 Volt

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Regular Charge Current (Ah)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)
								Length	Width	Height	Length	Width	Height	
12N5-3B	12	5	40	3.3	13.5	0.5	6	4 3/4	2 3/8	5 1/8	120	60	130	
12N5-4B	12	5	40	3.3	13.5	0.5	6	4 3/4	2 3/8	5 1/8	120	60	130	
12N5.5-3B	12	5.5	60	3.6	13.5	0.6	6	5 5/16	2 3/8	5 1/8	135	60	130	
12N5.5-4A	12	5.5	60	3.6	13.5	0.6	6	5 5/16	2 3/8	5 1/8	135	60	130	
12N5.5A-3B	12	5.5	44	4.0	16.9	0.6	6	4 1/16	3 9/16	4 1/2	103	90	114	
12N7-3B	12	7	90	4.0	16.9	0.7	6	5 5/16	3	5 1/4	135	75	133	
12N7-4A	12	7	90	4.0	16.9	0.7	6	5 5/16	3	5 1/4	135	75	133	
12N7-4B	12	7	90	4.0	16.9	0.7	6	5 5/16	3	5 1/4	135	75	133	
12N7D-3B	12	7	75	4.2	20.3	0.7	6	5 5/16	3	5 15/16	135	75	150	
12N9-3A-1	12	9	90	5.0	20.3	0.9	6	5 5/16	3	5 1/2	135	75	139	
12N9-3B	12	9	90	4.8	20.3	0.9	6	5 5/16	3	5 1/2	135	75	139	
12N9-4B-1	12	9	90	4.8	20.3	0.9	6	5 5/16	3	5 1/2	135	75	139	
12N10-3A	12	10	95	5.1	27.0	1.0	6	5 5/16	3 9/16	5 3/4	135	90	145	
12N12A-4A-1	12	12	113	6.3	23.7	1.2	6	5 5/16	3 3/16	6 15/16	134	80	160	
12N14-3A	12	14	128	7.0	27.0	1.4	8	5 5/16	3 1/2	6 9/16	134	89	166	
12N24-3	12	24	218	11.1	40.6	2.4	3	7 1/4	4 7/8	6 7/8	184	124	175	
CHD4-12 (H-12) U1(9)	12	30*	280	14.1	74.4	3.0	9	8 1/8	5 1/4	6 1/2	206	133	165	
U1(9)	12	24	200	11.3	60.9	2.4	14	7 3/4	5 1/4	7 1/8	196	131	181	

* @ 20 hr. rate

Battery Specifications - Import Automotive (NS Series)

Type	Voltage (V)	Capacity at 10HR (Ah)	CCA @ 0° F (-18° C)	Apprx. Weight w/o Acid (Lbs.)	Acid Volume (Oz.)	Terminal Type	Dimensions- Inches (+/- 1/16 In.)			Dimensions- Millimeters (+/- 2 mm.)			Assembly Figure (per cover polarity)	Handle Type		
							Length	Width	Height	Terminal Height	Length	Width			Height	Terminal Height
NS40Z	12	35	250	17	89	18	7 11/16	5/16	7 3/4	8 9/16	195	128	197	218		Plastic
NS40ZL	12	35	250	17	89	18	7 11/16	5/16	7 3/4	8 9/16	195	128	197	218		Plastic
NS40Z(S)	12	35	250	17	89	18	7 11/16	5/16	7 3/4	8 9/16	195	128	197	218		Plastic
NS40ZL(S)	12	35	250	17	89	18	7 11/16	5/16	7 3/4	8 9/16	195	128	197	218		Plastic
NS60	12	45	315	19	108	18	9 1/4	5 1/4	7 13/16	8 1/2	236	133	198	215		Plastic
NS60L	12	45	315	19	108	18	9 1/4	5 1/4	7 13/16	8 1/2	236	133	198	215		Plastic
NS60(S)	12	45	315	19	108	18	9 1/4	5 1/4	7 13/16	8 1/2	236	133	198	215		Plastic
NS60L(S)	12	45	315	19	108	18	9 1/4	5 1/4	7 13/16	8 1/2	236	133	198	215		Plastic
N100	12	85	630	38	239	18	15 15/16	6 13/16	8 1/8	9 1/8	405	173	206	232		Rope
N100L	12	85	630	38	239	18	15 15/16	6 13/16	8 1/8	9 1/8	405	173	206	232		Rope
N120	12	110	750	47	338	18	19 15/16	7 1/8	8 3/8	9 3/4	507	180	213	247		Rope
N120L	12	110	750	47	338	18	19 15/16	7 1/8	8 3/8	9 3/4	507	180	213	247		Rope
N200	12	170	1100	70	568	18	19 15/16	10 1/2	8 1/2	9 7/16	507	267	216	240		Rope
N200L	12	170	1100	70	568	18	19 15/16	10 1/2	8 1/2	9 7/16	507	267	216	240		Rope